

transform

your expectations



commercial doors





collaboration



A New Perspective

Opening up new possibilities and pushing the limits are easy with Clopay's diverse line of commercial doors. You'll have an award-winning selection to choose from that can help you redefine how others see your building.



on every level



When you choose Clopay for your commercial doors, you'll have access to a network of dealers who are ready to provide one-on-one collaboration. You'll work directly with a commercial door expert who will take the time to show you inspiring choices and help you reinvent your space with creative options. Whether your goal is to improve energy efficiency, let in more light or transform your space for a new application, Clopay will help you find the perfect solution on your terms.



Model 3720; Interior Shown with 24" x 8" Lites and 14 Gauge Hinges

Commercial-Grade Tools

Clopay collaborates with popular online resources to provide architects, specifiers, building owners and contractors the tools needed to properly specify commercial products and learn about LEED credits. Clopay offers Continuing Education with AIA certified courses on topics including wind load, fire doors and sectional door basics.

Need help with a specification?

Visit clopaycommercial.com or architectdoorhelp.com

Specification Tools



Building Information Management





explore your choices

Clopay offers a diverse selection of commercial doors that are uniquely suited to meet a wide array of specifications. Whether your primary need is durability, energy efficiency or versatility, Clopay has a door that will help you transform your space.



	ARCHITECTURAL SERIES Aluminum Full-View Doors	ARCHITECTURAL SERIES Steel Full-View Doors	ENERGY SERIES WITH INTELICORE® Polyurethane Insulated Steel Doors	ENERGY SERIES Polystyrene Insulated Steel Doors	INDUSTRIAL SERIES Ribbed Steel Doors	ROLLING STEEL SERIES Rolling Steel Doors	STACKING SERIES VertiStack™ Compact Vertical Stacking Sections	EXTREME™ SERIES High Performance Sectional Door System
--	--	---	--	--	---	---	---	---

EASE OF OPERATION	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★	★★★★★	★★★★★
APPEARANCE/DESIGN	★★★★★	★★★★★	★★★★	★★★★	★★★	★★	★★★★★	★★★★★
DURABILITY	★★★★★	★★★★★	★★★★★	★★★★	★★★	★★★★★	★★★	★★★★★
COST OF OWNERSHIP	\$\$\$	\$ \$	\$ \$	\$ \$	\$\$\$	\$	\$\$\$	\$ \$
ENERGY EFFICIENCY	★★	★★★★	★★★★★	★★★★	★★★	★★	★★	★★★
INITIAL COST	\$\$\$\$	\$\$\$\$	\$\$\$	\$ \$	\$ \$	\$\$\$\$\$	\$\$\$\$	\$\$\$\$

architectural series



Model 904, Clear Aluminum Doors; Shown with Tempered Insulated Glass

ALUMINUM FULL-VIEW DOORS

Clopay's Aluminum Full-View doors offer flexibility to allow varying degrees of light while complementing the surrounding structure. A wide selection of standard and custom glazing types and finishes make a bold statement in retail, service stations, restaurants and other environments requiring visibility or light.

MAXIMUM DURABILITY

- 2-1/8" (54 mm) thick section construction, 6063-T5 extruded aluminum alloy frame. Interior reinforcing fin standard on Model 904/904U where necessary.
- Tongue-and-groove meeting rail.
- Model 904/904U features contemporary boxed frame design with integral section joint seal.
- Model 904U features Intellicore® polyurethane insulated rails and stiles. R-value 3.8/U-factor 0.86 when glazed with clear insulated glass.

VERSATILITY AND DESIGN FLEXIBILITY

- Numerous glazing options include insulated, Low-E, frosted, mirrored, tinted and polycarbonate panels in various colors. Most glass types include tempered option.
- Wide variety of anodized, powder-coated and painted options, including Color Blast® Finish.
- 904U/904 has consistent panel widths and heights.

Calculated door section R-value is in accordance with DASMA TDS-163.



PANEL OPTIONS





GLASS/PANEL OPTIONS

						
Clear Glass	Gray Tinted Glass	Bronze Tinted Glass	Mirrored Glass*	Obscure Glass	Clear Laminate Impact Rated Glass†	White Laminate Glass*
						
Black Laminate Glass*	Frosted Glass or Acrylic	Clear Acrylic	Bronze Acrylic	Gray Acrylic	White Acrylic	Black Acrylic
			<p><i>*Mirrored and laminate not available in 1/2".</i> <i>†5/16" clear laminate impact rated glass is available only on 904W8/904UW8.</i> <i>Glass thickness available in 1/8", 1/4" and 1/2". Low-E available on insulated glass.</i> <i>Tri-wall polycarbonate thickness available in 1/2". Aluminum panels can be color matched to frame. Glass/acrylic panels may be combined with aluminum panels.</i> <i>Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit clopaydoor.com/acrylic for complete details.</i></p>			
Clear Polycarbonate	Bronze Polycarbonate	Aluminum Panel (Color-matched)				

FRAME/SOLID PANEL COLOR OPTIONS

						
Clear Aluminum (Anodized)	Standard White (Painted)	Bronze (Painted)	Chocolate (Painted)	Bronze (Anodized)**†	Black (Anodized)**	Dark Bronze (Anodized)**†

**Additional cost may apply.

†Due to the anodizing process, slight color variation may occur. The use of "Bronze (Painted)" is recommended for a more consistent bronze finish color. Custom powder coat and Color Blast® finish available. See your Clopay Dealer for details. Model 904U is not available with powder coat finish.

architectural series



Model 906U, Black Anodized Doors; Shown with Tempered Mirrored Glass

ALUMINUM FULL-VIEW DOORS

Clopay Models 905 and 906 are now available with a sleek panel design offering fewer lines and angles. The proportional rail and stile profiles, along with equal spacing, provide an aesthetically pleasing appearance. This sleek door is ideal in applications such as restaurants, auto dealerships and fire stations.

MAXIMUM DURABILITY

- 2-1/8" (54 mm) thick section construction, 6063-T5 extruded aluminum alloy frame. Interior reinforcing fin standard where necessary.
- Tongue-and-groove meeting rail.
- Models 905/905U/906/906U feature contemporary boxed frame design with integral section joint seal.
- Models 905U/906U feature Intellicore® polyurethane insulated rails and stiles.

VERSATILITY AND DESIGN FLEXIBILITY

- Glass types available include, acrylic, tempered, and insulated tempered glass. Glazing options available in low E, frosted, mirrored, and various colors.
- Wide variety of anodized, powder-coated and painted options, including Color Blast® Finish.
- 905/906 offers fewer stiles, creating a modern full-view aesthetic.



PANEL OPTIONS





PANEL CONFIGURATIONS

MODELS 905 AND 905U – 7'6" TO 8'5" HIGH DOORS




Up to 10'2" Wide
1 Panel

10'3" to 20'2" Wide
2 Panel

20'3" to 22'2" Wide
3 Panel

MODELS 906 AND 906U – 7'6" TO 8'5" HIGH DOORS




Up to 9'0" Wide
1 Panel


9'1" to 17'2" Wide
2 Panel

17'3" to 22'2" Wide
3 Panel

905/905U GLASS/PANEL OPTIONS



906/906U GLASS/PANEL OPTIONS



*Mirrored glass not available in 1/2".
Glass thickness available in 1/8", 1/4" and 1/2".
Low-E available on insulated glass.

Tri-wall polycarbonate thickness available in 1/2". Aluminum panels can be color matched to frame. Glass/acrylic panels may be combined with aluminum panels.
Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit clopaydoor.com/acrylic for complete details.

FRAME/SOLID PANEL COLOR OPTIONS



**Additional cost may apply.

*Due to the anodizing process, slight color variation may occur. The use of "Bronze (Painted)" is recommended for a more consistent bronze finish color. Custom powder coat and Color Blast® finish available. See your Clopay Dealer for details. Models 905U/906U are not available with powder coat finish.

architectural series

Model 3729; Shown with 42" x 16" Lites

STEEL FULL-VIEW DOORS

Clopay's Steel Full-View doors are durable, energy efficient and offer excellent visibility and design options. These doors are a perfect fit for commercial, retail, restaurant and industrial facilities where ease of maintenance, versatility, energy efficiency and durability considerations are all important.

MAXIMUM DURABILITY AND ENERGY EFFICIENCY

- Three-layer construction with thermal break section joints.
- 2" (50.8 mm) or 1-3/8" (34.9 mm) thick models with Intellicore® polyurethane or polystyrene insulation bonded to the interior and exterior steel skins.
- R-values up to 18.4*.

LOW MAINTENANCE WITH LASTING FINISH

- Hot-dipped galvanized steel skin with a baked-on primer and top coat.

VERSATILITY AND DESIGN FLEXIBILITY

- Injection-molded window frames with multiple glazing, size and visibility options.
- 37" x 8" contemporary slim window frame in black or silver aluminum. Many glass options available.
- Impact rated window options available.
- Minor ribbed or flush exterior skin.
- Variety of color options.


PEACE OF MIND

- Ten-year paint and delamination warranty†.

*R-value is impacted by the number of windows and window type per section. Calculated R-values for doors featuring a full row of windows, in both insulated and non-insulated glass, is available on our website. Calculated door section R-value is in accordance with DASMA TDS-163.

† Five-year delamination warranty for models 3159, 3158, 3209, 3209 and ten years for Models 3709, 3708, 3728, 3729.

PANEL OPTIONS



Minor Ribbed – Stucco Embossed
(3159, 3209, 3709, 3729*)



Flush – Stucco Embossed
(3158, 3208, 3708, 3728*)

*Exterior steel surface on a Lustra™ finish door has a smooth texture.

To view window glazing material options, see page 21.

WINDOW OPTIONS



19-1/2" x 16" – Injection Molded Frames
(3158, 3159, 3208, 3209, 3708, 3709, 3728, 3729)



42" x 16" – Injection Molded Frames
(3158, 3159, 3208, 3209, 3708, 3709, 3728, 3729)



37" x 8" – Slim Windows with Aluminum Frame
(3208, 3209, 3728, 3729)



Model 3208; Shown with 37" x 8" Lites



energy series with intellicore

POLYURETHANE INSULATED STEEL DOORS

Clopay's polyurethane insulated steel premier doors provide increased energy savings and advanced comfort using our innovative Intellicore® insulation technology. These doors are a smart choice for climate-controlled manufacturing facilities, warehouses, schools, office spaces and retail facilities.

MAXIMUM DURABILITY AND ENERGY EFFICIENCY

- Three-layer construction with thermal break section joints.
- 3" (76.2 mm), 2" (50.8 mm) or 1-3/8" (34.9 mm) thick models with Intellicore® polyurethane insulation bonded to the interior and exterior steel skins.
- R-values up to 27.2*.
- Exterior skin gauge options include 20, 24 or 27 gauge.

LOW MAINTENANCE WITH LASTING FINISH

- Hot-dipped galvanized steel skin with a baked-on primer and top coat.

VERSATILITY AND DESIGN FLEXIBILITY


- Injection-molded window frames with multiple glazing and window sizes. Aluminum full-view sections available in clear anodized and painted standard white and chocolate.
- Glazing options include DSB, tempered, plexiglass, insulated, insulated tempered and polycarbonate.
- Multiple steel texture embossments, panel designs and window options.
- Variety of color options.

PEACE OF MIND

- Ten-year paint and delamination warranty.

*Calculated door section R-value is in accordance with DASMA TDS-163.

PANEL OPTIONS



Minor Ribbed – Stucco Embossed
(3715, 3717, 3720, 3724, 3730)



Flush – Stucco Embossed
(3718, 3722)



Flush – Woodgrain Embossed
(3721)



Elegant Raised – Woodgrain Embossed
(3723)

WINDOW OPTIONS




24" x 8"
(3715, 3717, 3718, 3720, 3724, 3730)



24" x 12"
(3715, 3717, 3718, 3720, 3724, 3730)



Aluminum Full-View
(3715, 3717, 3718, 3720, 3724)



26" x 13" – Double Pane Polycarbonate Glazing
(3715, 3717, 3720, 3724)



19-1/2" x 12"
(3721, 3723)



40-1/2" x 12"
(3721, 3723)



Model 3724; Shown with 24" x 8" Lites

intellicore[®]
insulation technology



WARMER.
QUIETER.
STRONGER.

Commercial doors featuring Intellicore[®] insulation technology represent the ultimate smart choice. Clopay's Intellicore[®] insulation is a proprietary polyurethane foam that is injected into the door, expanding to fill the entire structure. The result is a door with incredible strength and durability. Its dense insulation also produces a quieter door, while its industry-leading R-values (up to 27.2) provide year-round comfort and improved energy efficiency.

durable and
energy efficient

energy series

POLYSTYRENE INSULATED STEEL DOORS

Clopay's Energy Series doors provide durability and enhanced comfort using our high-quality polystyrene insulation, three-layer construction and thermally broken section joints. These doors are an effective choice for industrial facilities, municipal buildings, warehouses and shipping docks under demanding conditions.

DURABILITY AND ENERGY EFFICIENCY

- Three-layer construction with thermal break section joints.
- 2" (50.8 mm) or 1-3/8" (34.9 mm) thick models with polystyrene insulation bonded to the interior and exterior steel skins.
- Exterior skin gauge options include 20, 24 or 27 gauge.
- R-values up to 9.1*.

LOW MAINTENANCE WITH LASTING FINISH

- Hot-dipped galvanized steel skin with a baked-on primer and top coat.

VERSATILITY AND DESIGN FLEXIBILITY


- Injection-molded window frames with multiple glazing and window sizes. Full-view section options in pre-painted Standard White or Chocolate available.
- Multiple steel texture embossments, panel designs and window options.
- Variety of color options.

PEACE OF MIND

- Ten-year paint and five-year delamination warranty.

*Calculated door section R-value is in accordance with DASMA TDS-163. Polystyrene CFC and HCFC free.


PANEL OPTIONS



Minor Ribbed – Stucco Embossed
(3150, 3200)



Flush – Stucco Embossed
(3220)



Flush – Woodgrain Embossed
(3155, 3211)



Elegant Raised – Woodgrain Embossed
(3154, 3213)

WINDOW OPTIONS



24" × 8"
(3150, 3200)



24" × 12"
(3150, 3200)



Aluminum Full-View
(3150, 3200)



19-1/2" × 12"
(3211, 3213)

To view window glazing material options, see page 21.

Model 3150; Shown with 24" × 8" Lites



3-layer bonded polystyrene doors are 2" or 1-3/8" sandwich construction

Model 520; Shown with 24" x 6" Lites

industrial series

RIBBED STEEL DOORS

Clopay's Industrial Series doors feature a variety of panel designs and a wide selection of steel gauges to meet your design, durability and budget requirements. These doors are a great choice for high traffic applications including industrial facilities, warehouses, distribution centers and loading docks.

DURABILITY AND ENHANCED COMFORT

- One or two-layer construction in 20, 24 and 25 gauge options.
- Two-layer models include polystyrene insulation with optional vinyl (524V, 525V and 664V) or steel back (520S, 522S, 524S and 525S).
- R-values up to 6.6*.

EASE OF MAINTENANCE WITH LONG LASTING FINISH

- Hot-dipped galvanized steel skin with a baked-on primer and top coat.

DESIGN FLEXIBILITY

- Multiple steel texture embossments and panel designs.
- Multiple window options. Full-view section options in pre-painted Standard White or Chocolate available.
- Variety of color options.

PEACE OF MIND


- Ten-year paint warranty.

*Calculated door section R-value is in accordance with DASMA TDS-163.




2" ribbed steel doors are available with polystyrene insulation or non-insulated

PANEL OPTIONS



Deep Ribbed – Smooth Embossed
(525, 524, 520)




Flush – Smooth Embossed
(522)



Classic Raised – Woodgrain Embossed
(664, 664V)

WINDOW OPTIONS



24" x 6"
(520, 522, 524, 525)



24" x 12"
(520, 522, 524, 525)



Aluminum Full-View
(520, 522, 524, 525)



19-1/2" x 12"
(664)


To view window glazing material options, see page 21.

STACKING SERIES



VERTISTACK™ CLEAR DOOR – MODEL VS904

The VertiStack Clear door utilizes unique, compact stacking sections that take up minimal ceiling space, so it won't interfere with mechanical, electrical or plumbing fixtures. Vertically stacked sections with minimal projection on the wall allow for a clear and open ceiling. The sections can even be recessed into the ceiling if desired. Designed to operate smoothly and quietly, the door will not disturb patrons when operating.




compact vertical stacking for an expanded footprint

BRINGING THE OUTSIDE IN

STANDARD COMPONENT MATERIALS AND FINISHES

1. **TORSION SPRINGS**
25,000-cycle springs
2. **STRAP SPOOL**
2" nylon strap in lieu of cable
3. **OPERATOR**
Side mount shown
Top and front mounts are also available
4. **GUIDE COVERS**
Slip-on design with no visible fasteners, powder coated in RAL 9005 (Jet Black)
5. **VINYL WEATHER SEAL**
Clips onto guide channel.
ASTM E283 Air Leakage Rating
6. **MANUAL LOCK**
Integrated into guide cover (1 per guide)
7. **SECTIONS**
Clear anodized aluminum (standard)
8. **HEADER CHANNEL**
For top seal contact, cable management and installation tool
9. **HEAD PLATES**
Powder coated in RAL 9005 (Jet Black)
10. **TOP SEAL**
Mounts to top section
11. **SHAFT COUPLER**



OPERATION AND STRUCTURAL REQUIREMENTS

Motor operation required.

The standard VertiStack operator includes an auxiliary hand chain for emergency use only. This product is supported by a guide assembly attached to the jamb construction. Header support is required for mounting counterbalance system as would be required with any standard sectional door. Adding an optional hood to a wider door may require hood supports.

OPTIONAL GLASS AND FINISHES


- A variety of glass and acrylic panels are available, including tempered, insulated, frosted and Low-E options available in thicknesses of 1/8", 1/4", 1/2" and 5/8"
- Anodized finishes: Clear, Black, Bronze, Dark Bronze
- Paint finishes: Chocolate, White and Bronze

AVAILABLE SAFETY FEATURES

- Photo eye sensors (concealed by guide covers)
- Wireless sensing edge (only available on doors over 53" high)

CERTIFICATIONS AND LISTINGS

- ±25 PSF Design Pressure – WindCode® W4
- Meets ASHRAE® 90.1, Title 24 and IECC® (International Energy Conservation Code) 2021 Section C406.9 Air Infiltration requirements with an independently tested value of 0.2 cfm/ft²



EXTREME SERIES

POWERED BY **LiftMaster**

COMPLETE EXTREME SERIES
DOOR SYSTEM INCLUDES:

CLOPAY COMMERCIAL DOOR

HEAVY DUTY COMPONENTS

DIRECT DRIVE OPERATOR



IDEAL FOR
EMERGENCY SERVICES,
MANUFACTURING,
DISTRIBUTION
AND AUTOMOTIVE
FACILITIES

HIGH PERFORMANCE SECTIONAL DOOR SYSTEM

The Clopay® Extreme™ Series High Performance Sectional Door System boasts an average opening speed of 24" per second, allowing productivity to flourish while also delivering the aesthetic you're looking for. Tandem nylon rollers improve roller life and reduce running noise for smooth, quiet operation while safety stays top of mind with enhanced features such as 3' of light curtain protection, a cable management system and standard cable tension monitors.

- Heavy duty components improve door life and promote smooth, quiet operation.
- Available as an insulated model to control temperature and noise reduction.
- Design pressures (DP) up to 36 PSF depending on door size, configuration and exposure. Models tested 50% greater than DP.
- 2 year/50,000 cycle warranty. *See warranty document for more information.*



EXTREME™ SERIES AVAILABILITY

architectural series



EX904, EX904U,
EX3728, EX3729, EX3708,
EX3709, EX3208, EX3209,
EX3158, EX3159,

energy series with intellicore



EX3724, EX3722,
EX3723, EX3721, EX3720,
EX3717, EX3718, EX3715

energy series



EX3200, EX3213,
EX3211, EX3220, EX3150

Visit clopaycommercial.com for series product details or for more information
reference product spreads throughout this brochure



Model EX904

24 IN/SEC OPENING SPEED

3x
FASTER*

THAN A TRADITIONAL SECTIONAL DOOR

**When compared to a 10' x 10' door with a Logic 5.0™ Operator set to an average of 8" per second*



POWERED BY LIFTMASTER®

The Extreme™ Series High Performance Sectional Door System features a direct drive operator with an opening speed of 24" per second and up to 600 cycles per day. The display's easy-to-read user interface provides ease of limit-setting at floor level and can connect to the operator via Wi-Fi to myQ® Facility.

SAFETY FEATURES



UL325 approved light curtain that reverses the door's downward motion when the beam is broken



Cable tension monitor that mitigates door operation when cable slackening occurs



Optional wireless bottom safety edge that reverses the door's downward motion upon contact with an object

PERFORMANCE REQUIREMENTS

Average Opening Speed	24" per second
Average Closing Speed	15" per second
Daily Duty Cycles	600 cycles/day
Max. Door Weight	1,000 lbs.
Warranted Cycles	600 cycles per day over 2-year warranty period
Drive System	Direct drive

Visit clopaycommercial.com for complete details or for more information scan the code shown



specialty sectional options

ADDITIONAL SECTIONAL DOOR OPTIONS



REPLACEMENT SLAB SOLUTIONS

Replacement slabs feature 1-5/8" (41.3 mm) thick, CFC-free polyurethane insulation with a 14.86 R-value*. A ribbed design and shiplap section joint make it a versatile replacement solution for many commercial service applications.

*Calculated door section R-value is in accordance with DASMA TDS-163.



BREAK-AWAY BOTTOM SECTION

Break-away bottom sections are excellent in high-traffic dock areas where damage to the bottom sections of doors is a common occurrence.



PASS DOOR

Pass doors are fitting for applications where space is too limited for the installation of a standard entry door. They conserve energy by allowing building access via a smaller opening versus the entire sectional door.



EXHAUST PORT

Can be cut into any type of sectional door. Available in 3" (7.6 cm) and 4" (10.2 cm) sizes.



SPRING BUMPERS

Standard on high lift and vertical lift tracks, optional on standard radius and low headroom tracks.



HIGH PERFORMANCE HARDWARE

High performance hardware features 10 gauge end hinges, heavy-duty top bracket and 3" (7.6 cm) sealed roller with 5/8" (15.9 mm) stem.



REMOVABLE CENTER MULLION

For openings that are wider than standard door width, consider using a carry-away, roll-away or swing-up mullion that enables two or more doors to close one opening.



SAFE-T-STOP™ CHAIN HOIST

Hand chain hoist with an integral braking system providing controlled descent for sectional doors.



EXTENDED 8-YEAR HARDWARE WARRANTY

Offers an 8-year limited warranty on all on-door hardware. Upgrades include 11 gauge hinges and 3" (76.2 mm) track.



ADAPTER RAILS

Shiplap to tongue-and-groove. 16' (4.9 m) length prepainted Standard White. 2" (50.8 mm) tongue-and-groove to tongue-and-groove. 16'2" (4.9 m) length prepainted Standard White or Chocolate.



GLAZING MATERIAL OPTIONS – SECTIONAL DOORS

ARCHITECTURAL SERIES STEEL FULL-VIEW, ENERGY SERIES WITH INTELICORE®, ENERGY SERIES AND INDUSTRIAL SERIES



Clear Glass



Frosted Glass



Obscure Glass



Narrow Reed Glass



Clear Acrylic

Tempered glass options available.

For full-view glass options, see Architectural Series Aluminum Full-View Door pages 7 and 9.

IMPACT WINDOW OPTIONS

ARCHITECTURAL SERIES STEEL FULL-VIEW AND ENERGY SERIES WITH INTELICORE®



Clear Polycarbonate



Bronze Polycarbonate



Matte
Polycarbonate



Pebble
Polycarbonate

COLOR OPTIONS – SECTIONAL DOORS



*Additional charges apply.
Due to the printing process, colors may vary.

	AVAILABILITY	Standard White	Almond	Desert Tan	Sandtone	Commercial Tan	Bronze	Chocolate	Mocha Brown	Hunter Green	Gray	Charcoal	Black	Trinar® White	Trinar® Beige	Lustra™ Black	Lustra™ Charcoal	Lustra™ Silver
ARCHITECTURAL SERIES	3158, 3159	■	■	■	■		■	■	■		■	■	■	■				
	3208, 3209	■						■			■	■	■	■				
	3708, 3709	■	■	■	■		■	■	■		■	■	■	■				
	3728, 3729	■	■	■	■		■	■	■		■	■	■	■		■	■	■
ENERGY SERIES WITH INTELLOCORE	3715	■				■		■	■		■	■						
	3717, 3718	■				■	■	■	■		■	■		■	■			
	3720	■				■	■	■	■		■	■		■	■			
	3722	■						■										
	3723, 3721	■	■	■	■			■				■						
	3724	■				■		■				■		■				
	3730	■						■										
ENERGY SERIES	3150	■				■		■	■		■	■		■				
	3200	■				■		■			■	■		■				
	3220	■						■										
	3154, 3155	■	■	■	■		■	■		■	■							
INDUSTRIAL SERIES	525, 525V, 525S	■						■						■				
	524, 524V, 524S	■				■		■			■			■				
	522, 522S	■						■										
	520, 520S	■						■										
	664, 664V	■	■	■	■			■										

For Models 904/904U color availability please refer to page 7. For Models 905/905U/906/906U color availability please refer to page 9.

CUSTOM PAINT OPTION

Color Blast® finish offers more than 1,500 Sherwin-Williams® color options to complement your building's color scheme. The resilient, two-part polyurethane-based paint system is specially formulated for excellent adhesion and stability on steel, aluminum, vinyl and plastics. This provides a high-quality, durable and professional finish for your garage door.

- Available on most sectional steel, overlay and aluminum commercial door models. (Not available on flush models 522 and 522S, commercial pass doors and breakaway bottom sections.)
- Backed by a five-year warranty.
- Meets American Architectural Manufacturing Association 2604 standards.
- Solar reflective paint technology results in lower surface temperatures compared with standard paints and may be required on some products to allow darker colors to be used.
- Provide the Sherwin-Williams® 4-digit color code to get started with your match.


Some colors may not be available as an exact match. These include, but are not limited to, some bright colors such as reds, blues and greens required in solar reflective formulation, metallic colors or non-solid colors like woodgrains.

For more information visit: www.clopaydoor.com/colorblast




FRAMING AND TRACK OPTIONS


JAMB TYPES *(shown from above)*




2" WOOD JAMB




3" WOOD JAMB




2" STEEL JAMB



3" STEEL JAMB




2" MASONRY JAMB




3" MASONRY JAMB


VERTICAL TRACK MOUNTING OPTIONS




2" BRACKET MOUNT



2" OR 3" CLIP MOUNT CONTINUOUS ANGLE



2" OR 3" CLIP MOUNT REVERSE ANGLE




3" FULL TAPERED REVERSE OR CONTINUOUS ANGLE

HIGH CYCLE SPRINGS



25,000, 50,000 or 100,000 cycle springs available.


STANDARD RADIUS



2" Track
 Headroom:
 12" Radius = 14-1/2" Required
 15" Radius = 16" Required
 Sideroom = 4-1/2" Required
 Backroom = Door Height + 23" Required

3" Track
 Headroom = 18" Required
 Sideroom = 5-1/2" Required
 Backroom = Door Height + 25" Required

HIGH LIFT




High lift equals distance from top of door to bottom of horizontal track.

2" Track
 Maximum high lift equals headroom available minus 14"
 Sideroom = 4-1/2" Required

3" Track
 Maximum high lift equals headroom available minus 15"
 Sideroom = 5-1/2" Required
 (Minimum high lift = 12" Required)


ROOF PITCH



2" Track
 Headroom = 16" Required
 Sideroom = 4-1/2" Required
 Backroom = Door Height + 23" Required

3" Track
 Headroom = 18" Required
 Sideroom = 5-1/2" Required
 Backroom = Door Height + 25" Required


VERTICAL LIFT



2" Track
 Headroom = Door Height + 12" Required
 Sideroom = 4-1/2" Required
 Backroom = 23" Required

3" Track
 Headroom = Door Height + 12" Required
 Sideroom = 5-1/2" Required
 Backroom = 23" Required


LOW HEADROOM FRONT MOUNT



2" Track
 Headroom = 12" Required
 Sideroom = 6" Required
 Backroom = Door Height + 23" Required

3" Track
 Headroom = 13" Required
 Sideroom = 6-1/2" Required
 Backroom = Door Height + 25" Required
 (1,200 lb. limit on door weight)


LOW HEADROOM REAR MOUNT



2" Track
 Headroom = 7-1/2" Required
 Sideroom = 6" Required
 Backroom = Door Height + 30" Required

3" Track
 Headroom = 10" Required
 Sideroom = 6-1/2" Required
 Backroom = Door Height + 32" Required
 (800 lb. limit on door weight)

HIGH LIFT WITH ROOF PITCH



2" Track
 Amount of High Lift + 16"
 Headroom = 16" Required
 Sideroom = 4-1/2" Required

3" Track
 Amount of High Lift + 18"
 Headroom = 18" Required
 Sideroom = 5-1/2" Required

Headroom = Top of door to nearest obstruction (truss)


Up to 4" of additional headroom may be required for a trolley door opener.

Note: These are general headroom requirements. Additional headroom may be required depending on door type, door height, drums, spring type or other options selected.

rolling steel series

ROLLING SERVICE DOORS


- Constructed of a high percentage of recycled material and designed with ease of maintenance and longevity in mind, increasing the sustainability of most applications.
- Curtains are available in prefinished galvanized steel, stainless steel or anodized aluminum finishes. Guides, bottom bars and headplates are powder-coat finished for aesthetics and increased durability.
- Practical innovations enhanced by the aesthetic appeal ensure that a Clopay door adds value to any building exterior, combining maximum security with modest operating costs.
- Doors can be operated manually with standard chain hoist, or they can be motor operated. Optional manual crank operation is also available.



SECURITY GRILLES

- After-hours security and space separation with visibility and air flow.
- Stainless steel, various anodized aluminum finishes and galvanized steel options.
- Standard pattern grille in 3" (7.6 cm), 6" (15.2 cm) or 9" (22.9 cm) vertical spacing. Popular brick pattern and glazed opening grilles.
- Structural self-supporting tubes available for installation of grille before storefronts or walls are installed.
- Provide security and access control in openings to 12' (3.7 m) high with low headroom conditions.
- Custom radii and angles offered.
- Offered in clear or color anodized finishes.
- Manufactured to the stringent qualities of the ISO 9001:2008 registered manufacturer.

GRILLE PATTERNS



Straight Pattern Grille
(2" x 3", 2" x 6", 2" x 9")



Brick Pattern Grille

rolling steel series

COUNTER SHUTTERS


- Manufactured to the stringent qualities of an ISO 9001:2008 registered manufacturer.
- Curtains are manufactured from 22 gauge stainless or galvanized steel, or 18 gauge aluminum.
- Operational choices include manual push-up, chain hoist, manual crank or electrical motor operation.
- The variety of installation options, product longevity and curtain options makes Clopay counter doors a great choice for informed design professionals.



FIRE-RATED DOORS AND SHUTTERS

- Manufactured to the stringent qualities of full-duty service doors, yet easily meet the most current fire protection standards.
- Operational choices include fail-safe, motor-operated systems, hand crank (manual) and standard chain hoist operated systems.
- UL, FM and ULC labeled for fire protection up to four hours to meet today's fire protection demands.
- Clopay fire doors and shutters may be easily and repeatedly drop tested and reset from the floor with no tool or equipment requirements.
- The service durability, simplicity of ownership and proven fire protection with E-Z reset option [standard on doors larger than 9' x 9' (2.7 m x 2.7 m)] make Clopay fire doors a logical choice for informed design professionals.

COLOR OPTIONS – ROLLING DOORS



White



Tan



Gray



Brown

Custom powder coat
RAL colors available.

Due to the printing process, colors may vary.

rolling steel series

ROLL-UP SHEET DOORS

Clopay Roll-Up Sheet Doors are low maintenance, have a long lasting finish and are designed for easy installation. These doors are ideal for mini-warehouse and storage facilities.

LOW MAINTENANCE WITH LASTING FINISH

- 26 gauge (24 for W8 WindCode® rating) hot-dipped galvanized steel curtain with a baked-on silicone polyester finish inside.
- Hot-dipped galvanized steel, roll-formed guides (18 gauge 150C, 16 gauge 157C and 12 gauge 160C).
- Self-lubricating wear strips on curtain prevent metal-to-metal contact, providing quieter operation.
- Heavy-duty bottom bar withstands the external elements.
- Full bulb bottom weather-strip helps ensure proper fit along irregular floors.

DESIGN OPTIONS

- Multiple color options.

PEACE OF MIND

- Forty-year chalking warranty, twenty-five year anti-fade warranty.
- Three-year hardware warranty (150C), one-year hardware warranty (157C, 160C).



CORRUGATED PANEL DESIGN

26 or 24 gauge steel, roll formed from ASTM A653 grade 80 full hard steel, interlocked and seamed together to make a continuous curtain for full height of door. *Model 157C shown.*



Model 157C, Roll-Up Sheet Door

COLOR OPTIONS – ROLL-UP DOORS

			
Glossy White	White	Silhouette Gray	Light Stone
			
Desert Tan	Sandstone	Bronze	Continental Brown
			
Maroon	Cedar Red	Valentine Red	Sierra Sunset
			
Sunset Orange	Teal	Dark Teal	Fern Green
			
Evergreen	Forest Green	Royal Blue	Polar Blue

Due to the printing process, colors may vary. Color availability may vary on WindCode® models.

All colors are backed by a film integrity warranty for 40 years guaranteed to hold up against cracking, checking or peeling. In addition, these colors are guaranteed not to chalk or fade for 25 years.

COMMERCIAL OPERATORS

LiftMaster®

GARAGE DOOR OPENERS



Clopay offers a full line of commercial openers designed to fit most applications.

- Jackshaft and trolley-driven openers to meet design and power requirements.
- Latest technology including MyQ® Technology to monitor or control the operator with Wi-Fi and smart phone capabilities.
- Available for single or three-phase power.
- Belt driven or gear driven to meet your specification requirements.
- Solenoid brakes are available on most models.
- Full line of safety equipment and accessories.

ACCESSORIES



- Sensing edges.
- Red/green traffic lights.
- Loop detectors.
- Damp environment/corrosion resistant modification.
- Many other modifications and accessories to meet your project requirements.

WINDCODE®

Clopay has been at the forefront of code compliant sectional door products for decades. From research and development to design assistance, Clopay is your source for WINDCODE® products. Clopay offers a variety of wind-loaded products in many different sizes and pressure ratings. Our continued emphasis on this important issue puts Clopay ahead of the competition.



Some of the benefits Clopay offers include:

- Professional engineering staff.
- Design recommendations.
- In-house testing facilities.
- Third-party independent testing verifications.
- Construction industry approvals: South Florida, Standard Building Code Congress, Texas Department of Insurance, North Carolina Building Code Council.
- In-house research and development at Clopay Building Products Technical Center in Cincinnati, Ohio.
- Dedicated building code product manager on staff.

architectdoorhelp.com

ARCHITECT RESOURCE GUIDE FOR GARAGE DOORS


Our Architect Portal is your go-to source for all the technical materials you need to support your next garage door project. You'll find residential and commercial overhead door resources like specifications, data sheets, a BIM library, and a custom drawing generator all in one place.

The screenshot displays the website's header with the Clopay Corporation logo and the title "ARCHITECT PORTAL". A navigation menu includes links for Home, Meet the Team, Commercial Download Library, Residential Download Library, Sectional Doors, Rolling Doors, Blog, and Call Today! (833.707.0082). A blue button reads "Need Help? Click Here!". Below is a featured banner for "STEEL INSULATED FULL VIEW DOORS" with a "LEARN MORE" button. A central heading asks "NEED THE RIGHT DOOR? WE CAN HELP!". Three categories are shown: Commercial Sectional Doors, Residential Sectional Doors, and Rolling Doors. A service menu offers Product Selection Help, Contact Architect Design Support, Technical Questions, Residential Download Library, Commercial Download Library, and Rolling Door Drawing Generator. A "NEED HELP?" section explains the free expert advice provided by the Architectural Design Support team.



upgrading expectations

Spokane International Airport Snow Removal Equipment Building



COLLABORATIVE DESIGN

Clopay partnered with a Master Authorized Dealer®, Continental Door Company, to design and install 28 commercial doors on Spokane International Airport's (SIA) new \$7.5 million snow removal building. The combination of Model 3722 overhead sectional steel doors and Model 903 full-view aluminum doors contributed to the building's LEED Gold certification and striking appearance.

ENGINEERED SOLUTION

Clopay engineers and the Continental Door team collaborated on designing doors to fit the installation challenges of the uniquely shaped building while delivering a solution that is extremely reliable, safe and efficient. The result is a visually stunning installation that features door hardware on a straight incline in lieu of a breakaway track, a custom staggered hinge scheme and 4' and 6' struts to meet demanding wind load requirements. The ruggedness of the 2" thick premium Model 3722, 20 gauge steel doors ensures low maintenance in an environment that is subjected to high traffic and harsh winter conditions.

CASE STUDY OVERVIEW:

- Location: Spokane, Washington
- Project Size: 46,400 square feet
- Facility Cost: \$7.5 million, LEED Gold certification
- Completion: June 2013
- Architect: Cortner Architectural
- General Contractor: Lydig Construction Inc., of Spokane
- Clopay Garage Door Installer: Continental Door Company

COMMERCIAL DOOR SELECTION CHART

ARCHITECTURAL SERIES (ALUMINUM FULL-VIEW DOORS)								
Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
904	–	Aluminum/Glass	–	2-1/8"	–	24'2"	20'0"	–
904U	–	Aluminum/Glass	–	2-1/8"	Intellicore® Polyurethane	24'2"	20'2"	3.8
905	–	Aluminum/Glass	–	2-1/8"	–	22'2"	16'0"	–
905U	–	Aluminum/Glass	–	2-1/8"	Intellicore® Polyurethane	20'2"	16'2"	–
906	–	Aluminum/Glass	–	2-1/8"	–	22'2"	16'0"	–
906U	–	Aluminum/Glass	–	2-1/8"	Intellicore® Polyurethane	20'2"	16'2"	–
ARCHITECTURAL SERIES (STEEL FULL-VIEW DOORS)								
Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
3158 [†]	Stucco	Flush	27	1-3/8"	Bonded Polystyrene	18'2"	16'0"	6.5 [‡]
3159 [†]	Stucco	Minor Ribbed	27	1-3/8"	Bonded Polystyrene	18'2"	16'0"	6.5 [‡]
3208 [†]	Stucco	Flush	24	2"	Bonded Polystyrene	20'2"	18'0"	9.1 [‡]
3209 [†]	Stucco	Minor Ribbed	24	2"	Bonded Polystyrene	20'2"	18'0"	9.1 [‡]
3708 [†]	Stucco	Flush	27	1-3/8"	Intellicore® Polyurethane	18'2"	16'0"	12.9 [‡]
3709 [†]	Stucco	Minor Ribbed	27	1-3/8"	Intellicore® Polyurethane	18'2"	16'0"	12.9 [‡]
3728 [†]	Stucco/Smooth	Flush	27	2"	Intellicore® Polyurethane	20'2"	18'0"	18.4 [‡]
3729 [†]	Stucco/Smooth	Minor Ribbed	27	2"	Intellicore® Polyurethane	20'2"	18'0"	18.4 [‡]
ENERGY SERIES WITH INTELLICORE								
Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
3715 [†]	Stucco	Minor Ribbed	27	1-3/8"	Intellicore® Polyurethane	18'2"	16'0"	12.9
3717 [†]	Stucco	Minor Ribbed	27	1-3/4"	Intellicore® Polyurethane	32'2"	26'0"	16.2
3718 [†]	Stucco	Flush	27	1-3/4"	Intellicore® Polyurethane	32'2"	26'0"	16.2
3720 [†]	Stucco	Minor Ribbed	27	2"	Intellicore® Polyurethane	40'2"	26'0"	18.4
3721 [†]	Woodgrain	Flush	27	2"	Intellicore® Polyurethane	24'2"	18'0"	18.4
3722 [†]	Stucco	Flush	20	2"	Intellicore® Polyurethane	40'2"	26'0"	18.4
3723 [†]	Woodgrain	Raised Panel	27	2"	Intellicore® Polyurethane	24'2"	18'0"	18.4
3724 [†]	Stucco	Minor Ribbed	24	2"	Intellicore® Polyurethane	40'2"	26'0"	18.4
3730 [†]	Stucco	Minor Ribbed	27	3"	Intellicore® Polyurethane	30'2"	18'0"	27.2
ENERGY SERIES								
Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
3150 [†]	Stucco	Minor Ribbed	27	1-3/8"	Bonded Polystyrene	18'2"	16'0"	6.5
3154 [†]	Woodgrain	Raised Panel	27	1-3/8"	Bonded Polystyrene	18'2"	16'0"	6.5
3155 [†]	Woodgrain	Flush	27	1-3/8"	Bonded Polystyrene	18'2"	16'0"	6.5
3200 [†]	Stucco	Minor Ribbed	24	2"	Bonded Polystyrene	26'2"	24'0"	9.1
3211 [†]	Woodgrain	Flush	24	2"	Bonded Polystyrene	24'2"	18'0"	9.1
3213 [†]	Woodgrain	Raised Panel	24	2"	Bonded Polystyrene	24'2"	18'0"	9.1
3220 [†]	Stucco	Flush	20	2"	Bonded Polystyrene	28'2"	26'0"	9.1
INDUSTRIAL SERIES								
Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
520 (S)	Smooth	Minor+Deep Ribs	20	2"	Polystyrene or Non-insulated	32'2"	26'0"	6.6**
522 (S)	Smooth	Flush	20	2"	Polystyrene or Non-insulated	24'2"	24'0"	6.6**
524 (S,V)	Smooth	Minor+Deep Ribs	24	2"	Polystyrene or Non-insulated	26'2"	24'0"	6.6**
525 (S,V)	Smooth	Minor+Deep Ribs	25	2"	Polystyrene or Non-insulated	20'2"	18'0"	6.6**
664 (V)	Woodgrain	Raised Panel	24	2"	Polystyrene or Non-insulated	20'0"	18'0"	6.3**
ROLLING STEEL DOORS								
Service Doors								
Model	Description	Insulation	Gauge	R-value	Slat Material			
CESD10	Heavy Duty Service Door	Non-insulated	18 to 24	–	Aluminum, Galvanized or Stainless Steel			
CESD20	Heavy Duty Service Door	Insulated	18 to 24	8.1	Aluminum, Galvanized or Stainless Steel			
CERD10	Heavy Duty Fire Rated Service Door	Non-insulated	18 to 22	–	Galvanized Steel or Stainless Steel			
CERD11	Heavy Duty Fire & Smoke Rated Service Door	Non-insulated	18 to 22	–	Galvanized Steel or Stainless Steel			
CERD20	Heavy Duty Fire Rated Service Door	Insulated	18 to 22	8.1	Galvanized Steel or Stainless Steel			
CERD21	Heavy Duty Fire & Smoke Rated Service Door	Insulated	18 to 22	8.1	–			
Security Grilles								
Model	Description	Pattern	Material					
CESG10	Rolling Grille	Standard	Stainless Steel or Galvanized Steel					
CESG11	Lexan™ Glazed Rolling Grille	Lexan™	Stainless Steel or Galvanized Steel					
CESG12	Rolling Grille	Brick	Stainless Steel or Galvanized Steel					
CESG30	Side Folding (accordion) Grille	Standard (9", 6" or 3" wide by 2" high)	Aluminum					
CESG31	Side Folding Lexan™ or Solid Grille	Solid or Lexan™	Aluminum					
Counter Doors								
Model	Description	Insulation	Gauge	R-value	Slat Material			
CESC10	Standard Counter Door	–	18 or 22	–	Aluminum, Galvanized or Stainless Steel			
CESC20	Standard Counter Door with Integral Frame	–	18 or 22	–	Aluminum, Galvanized or Stainless Steel			
CERC10	Standard Fire Rated Counter Door	–	22	–	Galvanized or Stainless Steel			
CERC20	Standard Fire Rated Counter Door with Integral Frame	–	22	–	Galvanized or Stainless Steel			
Rolling Sheet Doors								
Model	Description	Insulation	Curtain Gauge	Coil	Material			
150C	Light Duty	Available	26	9"	Galvanized Steel			
157C	Medium Duty	Available	26	12"	Galvanized Steel			
160C	Heavy Duty	Available	26	12"	Galvanized Steel			

*All widths may not be available in all heights. Consult the factory for more details. **For insulated models (S, V) only.

[†]Clopay complies with the 2015 IECC (International Energy Conservation Code) with an air infiltration rating of .40 cfm/ft² or less (IECC, Section 402.5.2), and also meets the U-factor requirement of .37 or less (IECC, Section C402.4, for Climate Zones 1 through 8).

[‡]R-value is impacted by the number of windows and window type per section.

Calculated R-values for doors featuring a full row of 3/4" (19.1 mm) insulated windows is available on our website.

COMMERCIAL SYSTEM SELECTION CHART

STACKING SERIES – VERTISTACK™ COMPACT VERTICAL STACKING SECTIONS

ARCHITECTURAL SERIES (ALUMINUM FULL-VIEW DOORS)

Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
VS904	–	Aluminum/Glass	–	2-1/8"	–	24'2"	20'0"	–

EXTREME™ SERIES – HIGH PERFORMANCE SECTIONAL DOOR SYSTEM

ARCHITECTURAL SERIES (ALUMINUM FULL-VIEW DOORS)

Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
EX904	–	Aluminum/Glass	–	2-1/8"	–	16'2"	14'0"	–
EX904U	–	Aluminum/Glass	–	2-1/8"	Intellicore® Polyurethane	16'2"	14'0"	3.8

ARCHITECTURAL SERIES (STEEL FULL-VIEW DOORS)

Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
EX3158	Stucco	Flush	27	1-3/8"	Bonded Polystyrene	16'2"	14'0"	6.5 [‡]
EX3159	Stucco	Minor Ribbed	27	1-3/8"	Bonded Polystyrene	16'2"	14'0"	6.5 [‡]
EX3208	Stucco	Flush	24	2"	Bonded Polystyrene	16'2"	14'0"	9.1 [‡]
EX3209	Stucco	Minor Ribbed	24	2"	Bonded Polystyrene	16'2"	14'0"	9.1 [‡]
EX3708	Stucco	Flush	27	1-3/8"	Intellicore® Polyurethane	16'2"	14'0"	12.9 [‡]
EX3709	Stucco	Minor Ribbed	27	1-3/8"	Intellicore® Polyurethane	16'2"	14'0"	12.9 [‡]
EX3728	Stucco/Smooth	Flush	27	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4 [‡]
EX3729	Stucco/Smooth	Minor Ribbed	27	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4 [‡]

ENERGY SERIES WITH INTELICORE

Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
EX3715	Stucco	Minor Ribbed	27	1-3/8"	Intellicore® Polyurethane	16'2"	14'0"	12.9
EX3717	Stucco	Minor Ribbed	27	1-3/4"	Intellicore® Polyurethane	16'2"	14'0"	16.2
EX3718	Stucco	Flush	27	1-3/4"	Intellicore® Polyurethane	16'2"	14'0"	16.2
EX3720	Stucco	Minor Ribbed	27	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4
EX3721	Woodgrain	Flush	27	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4
EX3722	Stucco	Flush	20	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4
EX3723	Woodgrain	Raised Panel	27	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4
EX3724	Stucco	Minor Ribbed	24	2"	Intellicore® Polyurethane	16'2"	14'0"	18.4

ENERGY SERIES

Model	Steel Emboss	Exterior Skin Pattern	Gauge	Section Thickness	Insulation	Max. Width*	Max. Height*	R-value
EX3150	Stucco	Minor Ribbed	27	1-3/8"	Bonded Polystyrene	16'2"	14'0"	6.5
EX3200	Stucco	Minor Ribbed	24	2"	Bonded Polystyrene	16'2"	14'0"	9.1
EX3211	Woodgrain	Flush	24	2"	Bonded Polystyrene	16'2"	14'0"	9.1
EX3213	Woodgrain	Raised Panel	24	2"	Bonded Polystyrene	16'2"	14'0"	9.1
EX3220	Stucco	Flush	20	2"	Bonded Polystyrene	16'2"	14'0"	9.1



Model 3729; Shown in Lustra™ Silver Finish with Full-View Lites

Model 3708; Shown with 42" x 16" Lites

finding the right solution

Find Your Solution With Clopay



Our team of Clopay commercial door experts is always ready to assist. To find the Clopay commercial door that's right for your application, visit clopaycommercial.com or architectdoorhelp.com. To locate a dealer go to clopaydoor.com/where-to-buy/commercial or call 1-800-2CLOPAY (225-6729).



©2023 Clopay Corporation. All rights reserved.

CMDC-IDEA-15_REV0723